

Model	NBQ1600W-EU	NBQ2000W-EU
Input part (DC)		
Recommended solar panel input power		275-530W×4
Number of DC input connections		MC4*4
Maximum input voltage		60V
DC voltage input range		16~60V
Start-up voltage		22v
MPPT tracking range		22~55V
MPPT efficiency		>=99.5%
Maximum input DC current	14A*4	16A*4
Output parameters(AC)		
Maximum output power	1600W	2000W
Rated output voltage		230V
AC voltage range		190-270V
Maximum output current	6.95A	8.69A
Rated output frequency		50Hz/60Hz
Output frequency range		47.5-50.5Hz/58.9-61.9Hz
Harmonic distortion		<5%
Output power factor		>0.99
Maximum conversion efficiency		96%
Protection level		Class I
Protection function		
Oversupply/undervoltage protection		YES
Over-frequency/under-frequency insurance Protect		YES
Anti-island effect protection		YES
Overcurrent protection		YES
Overload protection		YES
Over-temperature protection		YES
Protection level		IP67
Operating temperature range		-40°C to +65°C
Indicator	light Working status light + Wi-Fi signal light	
Communication mode	Wi-Fi / 2.4G	
Cooling method	Natural cooling (fanless)	
Working environment	Indoor/outdoor	
Weight	5.2kg	
Size (L*W*H)mm	342mm*225.4*50mm	
Complies with the standard	VDE:VDE-AR-N 4105;CE-LVD:EN50549; EN62109-1/-2;ROHS:IEC62321,	